


# RAVENHILL STUDIO

2122 Cypress Ave, Los Angeles, CA 90065  
323.977.8532, contact@ravenhillstudio.com



We recommend finding a clean and level surface to assemble this fixture and consider having a helper nearby in case you need an extra set of hands.

Your Slide Floor Lamp 16 comes packaged in (5) individual parts packaged in 2 separate boxes:

## (1) Floor Lamp Assembly

Socket  
(2) Uno Socket Rings  
Thumb Screw Swivel  
Stem (Outer Tube)  
Inner Tube  
Telescoping Clutch

## (1) Base Assembly

Bushing  
Reducer  
Concrete Base  
Cord and Plug

## (1) Shade Assembly

Shade  
Uno Socket Bracket  
Shade Finish Nut  
Shade Hex Cap

## (1) Misc Contents Envelope

Nitrile Gloves  
(Recommended for installation)  
Installation Instructions  
Loctite  
Protective Cover


## (1) Lightbulb


Included with your Slide fixture is a 7 watt LED bulb.

It is a warm white (2700K) G25 bulb with an output of 800 lumens.

The bulb is JA8 certified and has a 15,000 hr lifetime.

G25 recommended. 10W Max


 **CAUTION:** Before starting, turn off power at main circuit power.



Your Slide 16 Floor Lamp Assemblies are joined together as shown in the picture above.


Your Slide 2 Arm fixture includes a fabric covered Shade which is vulnerable to staining if care is not taken. Before installing or adjusting your Slide fixture it is highly recommended to clean hands and wear gloves and to only adjust the Slide Shade as described in notes below. Failure to do so may result in smudges or stains.

1. Unpack the box containing the Shade Assembly and set aside Shade Assembly on a clean even surface.
2. Unpack the Miscellaneous Contents envelope, and put on the included Nitrile Gloves.
3. In order to remove fixture from the packaging you must first identify the boxes labeled Base and Stem.




\*\* this box cannot be removed as it is attached to the outer box


4. First, cut open the box labeled Base and remove the bubble wrapped Concrete Base along with the attached cord and set it on the ground.
5. Grab the box labeled Stem and slide up the box out of the way. Keep the foam packaging on for now.
6. Place the Concrete Base upright on top of a level and even surface.
7. Slide the foam packaging off of the tube partially to gain access to the Telescoping clutch near the top of the Stem. Unscrew the Telescoping Clutch by loosening the top portion to disengage the clutch.




8. Now prepare to assemble the Stem onto the Concrete Base. Remove the extra slack of wire connecting the two assemblies by pushing it back through the bushing.




9. Place the included Protective Cover onto the base. Make sure to line it up with the hole and that it is sitting flush with the base.




10. Place a few (3-4) drops of loctite onto the threads of the base (be careful to not use too much glue).




11. Screw the Stem onto the Base and tighten it all the way. It can take 24 hours for the glue to dry, so avoid stressing this connection until glue is fully cured.




12. Clean up excess loctite from the base with a rag, then remove the protective cover for the base.
13. Raise the Inner Tube to the desired height and tighten back the Telescoping Clutch.
14. Loosen the Thumb Screw Swivel and position the Socket to be angled at roughly 45 degrees.



15. Install the Shade by first removing the outer Uno Socket Ring from the Socket and placing the shade-mounted Uno Socket Bracket onto the Socket threads. Thread the Uno Socket Ring back onto the Socket, and making sure that the Shade is visually level side to side, tighten down the Uno Socket Ring to secure the Shade Assembly.



16. Make any final front to back level adjustments by loosening the Thumb Screw Swivel to adjust the forward/backward tilt of the Shade. Small side to side Shade adjustments can be made by grabbing the bottom of Shade to adjust. Larger side adjustments would require the Uno Socket Ring to be loosened first.



17. Remove foam wrapping of the Stem by carefully peeling the red packing tape.

18. Install Lightbulb and enjoy!

#### NOTES / TROUBLESHOOTING:

Make sure to fully tighten the Thumb Screw Swivel after finalizing shade orientation to ensure Shade doesn't move over time.

If your Slide Floor Lamp Shade is not perfectly level it may be necessary to loosen the Thumb Screw Swivel and Uno Ring to get the desired orientation.

To clean your Slide Shade it is recommended to use compressed air to blow away dust and dirt particles. Avoid using water or a vacuum to clean your Slide Shade.

Due to the delicate nature of the fabric covered Shades it is highly recommended to clean hands and wear gloves before installing or adjusting your Slide fixture.