



PIVOT SCONCE

The simple armature of the Pivot Sconce rotates freely from a wall-mounted bracket. The sconce features an adjustable spun shade cradled in a cast collar which can be pivoted to provide light where needed. Available hardwired in 18", 24", 36", and 48" lengths.

CARE | Clean with soft microfiber cloth which can be dampened if necessary.

DIMENSIONS/ WEIGHT

6" x 18" x 8"
6" x 24" x 8"
6" x 36" x 8"
6" x 48" x 8"
3.5-4.5 lbs

WALL PLATE

4.5" x 8.5", Screw holes 2.75" apart

BULB/ TECHNICAL SPECS

E26 G25 LED 6W DTW bulb
2700K-1800K, 90+CRI, 480 Lumens
Bulb lifespan 15K hours
7W, 2700K, 800 Lumens
90+CRI, bulb option available

CERTIFICATION

UL, cUL
JA8 Compliant

VOLTAGE

120V/ 220V

FINISH OPTIONS

White & Brass, White & Stainless,
Black & Brass, Black

J-BOX SPECS

Fits Sconce J-Box with horizontal
mounting screws 2.75" apart and
wall cutouts under 4" DIA

DIMMABILITY

CL Dimmers Recommended
Dims to 10%
Recommended Models:
Lutron Diva: DVCL-153P
Lutron Skylark: SCL-153P
Lutron Maestro: MACL-153M

RAVENHILL STUDIO

323. 977. 8532
contact@ravenhillstudio.com